

ACRYL 600

PRODUCT

Quick drying acrylic spray paint.

PROPERTIES AND FIELDS OF USE

Non-yellowing solvent-based acrylic paint for professional and hobby use. For indoor and outdoor. Excellent resistance to atmospheric agents and light. Over-paintable. Ideal for: INDUSTRY - CRAFTS - DIY.

SURFACES

High adhesion on several supports such as metal (iron, brass, steel), ABS plastics (no PP or similar), wood, glass, stone, cement. For plastic surfaces, apply the plastic primer beforehand. Incompatibility: do not apply on surfaces with residues of products containing silicones. Do not apply on polystyrene. Application on synthetic paints is not recommended.

TECHNICAL SPECIFICATIONS

Binder	Modified acrylic
Yield	1,5-2 m ²
Pressure at 20 °C	Da 4.2 a 4,8 bar
Pressure at 50 °C	Da 7.6 a 8.4 bar
COV	see SDS Sec. 9.1 and 15.3
Gloss level:	
Gloss	80-85 gloss at 60°
Satin	20-40 gloss at 60°
Matt	5-15 gloss at 60°
Maximum temperature:	90-100°C
Drying time:	
Dust-free	5-8 minutes
Dry to touch	15-20 minutes
Deep dry	16-20 hours

INSTRUCTIONS FOR USE

Before use carefully read the instructions on the can and consult the SDS for safe handling of the product (Sec. 7.1).

Use between 10 and 25 °C on surfaces at the same temperature, in well ventilated environments. Mask the parts not to be treated. Remove residues of rust or paint not anchored. Degrease. Shake the can vigorously for approx. 2 minutes from the moment you feel the mixing balls. Make a spray test on a separate surface. Spray a layer in cross coats, from a distance of 20-25 cm. If necessary repeat the application after about 15 minutes. On plastics we recommend the use of the special primer. To level the surfaces use the filler base in advance. Every time you finish the application, turn the can upside down and spray for a few seconds until the product comes out so you can clean the spray-head.



Sede Legale, Amministrativa e Operativa: Via Benvenuto Cellini 26, 20033 Solaro (Mi)

C.C.I.A.A. Milano 1172121

Codice fiscale e Partita IVA: 01485370124

Capitale sociale: Euro 1.000.000,00 interamente versato

Contacts: Phone: +39 02 9690664 Fax: +39 02 9691714

Website: www.colorpack.com Email: info@colorpack.com

SDI CODE: BY5KTZZ

For further information refer to the SDS: labelling (Sec. 2.2), storage (Sec. 7.2) and disposal (Sec. 13).

EXEMPTION FROM LIABILITY

The information contained in this document is provided to the best of our scientific knowledge. However, they should be regarded as non-binding indications and do not release the consumer from personally carrying out checks on the products as to their compatibility with their intended uses. Colorpack Srl is relieved of any liability if any damage is not link to specific causes attributable to the same Colorpack Srl.

THE LABORATORY/QMS



Sede Legale, Amministrativa e Operativa: Via Benvenuto Cellini 26, 20033 Solaro (Mi)

C.C.I.A.A. Milano 1172121

Codice fiscale e Partita IVA: 01485370124

Capitale sociale: Euro 1.000.000,00 interamente versato

Contacts: Phone: +39 02 9690664 Fax: +39 02 9691714

Website: www.colorpack.com Email: info@colorpack.com

SDI CODE: BY5KTZZ